An ISO 9001 : 2015 Company

**SINCE 1999** 





## CATALOG FOR COMPLETE AUTOMATIC COMPRESSION TESTING MACHINES

# K.J.INTERNATIONAL

**Specialist in Mfg. & sales of :** Testing instruments for Cement, Concrete, Soil, Materials, Laboratory, NDT, Measuting & Survrying Instuments (Also Dealing in Electronics & plastic Testing Instruments)

#### **CORPORATE OFFICE AND WORKS:-**

45, Union industrial eastate,Nr. Rameshwar parks B.R.T.S. station, N.H.-8,Opp. Shivanand nagar, Rajendrapark - Nagarwel hanuman mandir road,Rakhia,Ahmedabad - 380023, Gujarat, India. E-MAIL:- jagannath\_kj2000@yahoo.co.in, kjint219@gmail.com Website:- www.kjinternational.in

PH: 079-22910180, Mo: 09824252066, Mo: 09824197066

*"KJ International is our Sister Concern Company of K.J Enterprise"* "R.D.Calibration and Consultancy" CATALOG FOR COMPLETE AUTOMATIC COMPRESSION TESTING MACHINES RANG 0 - 3000KN An ISO 9001 : 2015 Company

**SINCE 1999** 



# SPECIFICATION :

- PILOT smart automatic COMPRESSION TESTING MACHINE 3000KN IS frame. (Both in international AND IS Standards.). (Avalable in all range from 50 kn to 5000 kn)
- PILOT control unit.
- > Comprehends: Control head and hydraulic power unit. 230V/50-60Hz/1PH.
- Along with 82-P0700 pressure transducer 0-700 bar and 82-P0349/ELT connecting cable for pressure transducer.

n ISO 9001 : 2015 Com

**SINCE 1999** 

- > Automatic pace rate control variable .
- > Large touch screen display with both numeric and graphical with so many parameters inputs.
- > An Energy saving technology .
- > LAN port for PC connection and USB port for easy data storage on pen-drive.
- > Advanced electronics ensuring superior precision and high stability effective resolution.
- Compatible with 82-SW/DM data manager software for real time acquisition and management of test data (optional).
- > Second frame option 50-C10C/2F (Optional).
- > The PILOT Smart-line stand-alone console can control lexural and compression testing frame from 15 to 4000 KN cap.
- Hydraulic: Dual stage pump with DC motor, Energy saving technology to reduce the power consumption and <u>ensure silent operation</u>.
- Hardware: 132,000 points effective resolution, touch screen graphic display 240x128 pixel, sampling rate 50/sec, large storing capacity on USB pen drive



- downloadable to PC, Ethernet port, real time management software (optional).
- Firmware: Simultaneous display of load-specific load, Actual Load Rate and Load/Time Graph; LAN Connection to PC; Advanced Memory Management; Multi Coefficient Calibration.
- Available in all ranges 100, 250,500,1000,2000,3000 kn, also attachable for Flexural test by extra output control valve.
- Testable specimens, cube moulds, 50x50, 70.6x70.6, 100x100,150x150, 200x200 MM, Cylinder Moulds 100x200, 150x300 MM, Rectangle Moulds , Bricks, Blocks, and different sized Roacks ETC....
- > Operates on single phase 240 volts supply.

### Optional Accessory

- > DATAMANAGER PC software compatible with DIGIMAX,
- > PILOT and AUTOMAX SMART Line. Suitable for remote
- Control of the system (AUTOMAX only),
- > Data Acquisition, processing and filing. Printout of customized test certificates.

### -: End of the catalog :-